

NEW PRODUCT ANNOUNCEMENT



The Nady UHF 802 Platinum Series

The new 2 channel Nady Platinum wireless system offers flawless performance and sound on the uncluttered UHF band at an incredibly new low price.

- Both transmitters and receivers offer 2 user switchable channels for enhanced versatility and optimum interference free operation in any locale.
- Choice of durable metal handheld microphone, lavalier, headmic, or instrument bodypack transmitters.
- Space saving Nady 802 receiver is ultra compact and rackmountable (with optional kit) and features dual antennas and DigiTRU Diversity™ with advanced digital processing circuitry for maximum range and elimination of dropouts in adverse RF conditions. Also features both adjustable line level 1/4" and fixed mic level XLR outputs.
- Nady's renowned industry-best 120 dB dynamic range for the clearest, quietest, most natural sound in wireless.
- 250 ft. range typical—up to 500+ feet line-of-sight.

A major breakthrough in affordable UHF frequency agile technology, the Nady Platinum 802 system is the best value available in professional wireless systems.

NADY 802 SYSTEM SPECIFICATIONS

OVERALL SYSTEM PERFORMANCE

Frequency Response: 25-20,000 Hz, ± 3 dB
Dynamic Range: 120 dB
Harmonic Distortion: < 0.5%
Modulation: FM ± 20 KHz.
Operating Range: 250 feet typically;
up to 500+ feet line-of-sight

NADY 802 TWO CHANNEL UHF TRANSMITTERS

Controls: Nady HT-5 Handheld: ON/OFF,
Audio ON/OFF, Channel Selector, Input level
adjust.

Nady GT-5 Instrument, LT-5 Lavalier, and SX-5
bodypack: OFF/STANDBY/ON, Channel
Selector, Input Level Adjust.

LED Indicator: Unit "ON" (single flash); Low
Battery Alert (steady).
RF Power Out: 50 mW nominal (maximum
allowed by FCC).
Harmonic and Spurious Emissions: < -40 dBc.
Battery: 9V alkaline.
Battery Life: 10-12 hours
Also available: Optional: Nady SX-5 bodypack
transmitter with mini XLR connector for electret
condenser lavalier or microphone or headmic.

NADY 802 TWO CHANNEL UHF RECEIVER

Controls: Power ON/OFF, Volume Control,
Mute Adjust, Channel Selector.

Connectors: Audio Outputs: nominal line level
1/4" mono phone jack and mic level XLR. DC
Input: 3.5 mm mini jack.
LED Indicators: Power "ON"; Transmitter "TX";
ch. A "ON" and ch. B "ON".
Mute: Externally adjustable with preset
minimum.
Unwanted Signal Rejection: 60 dB image and
spurious.
802 Dimensions: 7" x 5" x 1.25"
802 Weight: 19 oz.
Power Requirements: 12V DC @150 mA, tip
positive.
Antennas: (Dual) DigiTRU Diversity™.



Nady Systems, Inc. • 6701 Shellmound Street, Emeryville, CA 94608 • 510/652-2411 • FAX: 510/652-5075 • www.nadywireless.com

Specifications are subject to change without notice. Copyright ©1998 Nady Systems, Inc. 6/98