

SPA Series Professional Power Amplifiers

Offering top power, superior performance and full professional operating features in a roadworthy compact chassis, the SPA Series are perfect for even the most demanding sound reinforcement installation and touring applications.



SPA 850

2 X 350W @ 4 Ω, 2 X 425W @ 2 Ω
Bridged mono: 600W @ 8 Ω, 850W @ 4 Ω



SPA 1400

2 X 500W @ 4 Ω, 2 X 800W @ 2 Ω
Bridged mono: 1000W @ 8 Ω, 1400W @ 4 Ω



SPA 2400

2 X 750W @ 4 Ω, 2 X 1400W @ 2 Ω
Bridged mono: 1600W @ 8 Ω, 2400W @ 4 Ω

- Continuously variable speed fan with back-to-front air flow
- Full operating features: user-defeatable clip limiter; switchable 30Hz low-cut filter; balanced XLR and 1/4" TRS inputs; detent volume controls; stereo (dual-channel), parallel-input, or bridged mono operating models with selector switch; binding post and Neutrik Speakon™ outputs; ground-lift switch
- Complete, advanced safety/reliability features: soft-start turn on; noise-free on-off; built-in DC offset; independent DC and thermal overload protection on each

channel; short circuit and speaker protection; DC servo operation; built-in current limiter

- Parallel outputs allow "daisy chaining" amps
- ~115V (60Hz)/~230V (50Hz) AC select switch
- Clip and Signal LED indicators for each channel
- Durable double rack space (2U) steel casing

XA Series Professional Power Amplifier

Offering top performance and high-end stereo amp features at the lowest dollar per Watt pricing available, the XA-1100 is the best value in amplifiers on the market.

- Full operating features: detent volume controls; parallel balanced XLR and 1/4" TRS inputs; stereo (dual channel), parallel-input, or bridged mono operating modes with selector switch; binding post (banana plug) outputs; ground lift switch
- Full safety/reliability features: 2 dual speed fans for cooling; soft-start turn on, noise-free on-off; built-in DC offset; independent DC and thermal overload protection on each channel; short circuit and speaker protection; DC servo operation; built-in digital current limiter
- Power ON, Clip, Signal, and Protect LED indicators for each channel
- Roadworthy, rugged double rack space (2U) housing
- ~115V(60Hz)/~230V(50Hz) AC select switch and IEC power cord connector with built-in fuse



XA-1100

2 X 500W @ 4 Ω, 2 X 730W @ 2 Ω
Bridged mono: 1100W @ 4 Ω

SRA Series Professional Power Amplifiers

Compact, full-featured and versatile, the SRA Series provides studio quality audio for project recording and live applications.



SRA 2150

2 X 150W @ 4 Ω 250W mono bridged @ 8 Ω



SRA 2250

2 X 250W @ 4 Ω 350W mono bridged @ 8 Ω

- Convection cooled with no fan for quietest operation
- Full convenience features: calibrated 41 detent volume controls, headphone output with speaker-disable switch for private monitoring, switchable Low Cut filters for eliminating speaker rumble and resonance, switchable 2/4/8 ohm operation, and stereo/mono-bridged switch
- 1/4" TRS and XLR balanced and RCA unbalanced inputs, 1/4" and binding post (banana jack) speaker outputs

- ~115V (60Hz)/~230V (50Hz) AC select switch
- Complete, advanced safety and reliability features: soft-start turn on; noise-free on/off; built-in DC offset, short circuit, and speaker protection; built-in current and signal voltage limiters.
- Peak, Power/Protection, and Signal LEDs for each channel
- Rugged single rack space (1U) steel housing