

FS-4N SPECIFICATIONS

INPUT CONNECTOR:	One 1/4" TRS phone jack
INPUT SENSITIVITY:	0.775 (0dBm)
INPUT IMPEDANCE:	15 K ohm balanced
OUTPUT CONNECTOR:	One 1/4" TRS phone jack
OUTPUT LEVEL:	0.775 (0 dBm)
OUTPUT IMPEDANCE:	600 OHM BALANCED
FREQUENCY RESPONSE:	20Hz~20KHz, < ± 1.0 dB
SIGNAL-TO-NOISE RATIO:	> 68 dB
T.H.D.:	< 0.4%
NOTCH FILTER FREQUENCY RANGE:	60 HZ ~ 6 KHz, continuously variable
NOTCH DEPTH:	0 ~ -20 dB
POWER CONSUMPTION:	5.5 Watts
POWER SOURCE:	AC: 120V/230V, 50/60 Hz; DC: 24V
FUSE REQUIREMENTS:	120 VAC: 0.315 A / 250V; 230 VAC: 0.2A / 250V
DIMENSIONS:	19" X 1.75" X 8.3" (483 X 44 X 210mm), 1U rack height
WEIGHT:	6.6 lbs (3.0 Kg)

Note: *For improvement purposes, specifications, design and appearance are subject to change without prior notice.*