

HPA-4 SPECIFICATIONS

AUDIO INPUTS

Connectors 1/4" jack
Type Unbalanced
Impedance 47k Ohms
Peak input level +25dB
Gain control range +35dB

HEADPHONE POWER AMPLIFIER OUTPUTS

Max. output level 300mW@32 Ohms (max 1W @ 32 Ohms)
Output impedance 22 Ohms
Max. gain +20 dB

LINE DISTRIBUTION OUTPUTS

Connectors 1/4" jack
Type Unbalanced/Parallel

DISTORTION, FREQUENCY RESPONSE, S/N RATIO & CROSSTALK

Distortion 0.02%
Frequency response 20Hz~20kHz, 0dB~-2B
S/N Ratio Better than 80dB
Crosstalk rejection >68dB@1kHz; 20dBinput

FUNCTION CONTROLS

Volume Per channel, variable
Signal selectors Per channel, Variable

POWER SUPPLY

AC requirements Selectable, ~100-120 VAC,
~ 200-240V AC, 50-60 Hz
Power consumption 11.5VA
Fuse 100-120 VAC: 630 mA (slow-blow)
200-240 VAC: 315 mA (slow-blow)
100-240 VAC: 500 mA (slow-blow)
5X20mm glass type
Power cord connector Standard IEC receptacle
with built-in fuse holder

PHYSICAL

Dimensions 1.75"X 19"X 8.5"(44.5X482.6X217mm)
Weight 6.93lbs (3.15Kg)

The specifications above are correct at the time of printing of this manual. For improvement purposes, all specifications for this unit, including design and appearance, are subject to change without prior notice.