

MPM 880 SPECIFICATIONS

Output Power80W music peak power at 8Ω, 100W at 4Ω, each speaker output

Frequency Response30Hz-13KHz +/-3dB

Total Harmonic Distortion (THD) + Noise.....< 0.85%

Inputs (max. sensitivity/impedance).....8 X MIC: 6mV / 1KΩ
8 X Line: 60mV / 15KΩ
1 X Return: 800mV / 15KΩ
4 X CD/TAPE: 300mV / 25KΩ

Outputs (max.out/impedance).....1 X Send: 850mV / 100K

Output Equalization±10dB, 5 bands at 100Hz, 330Hz, 1KHz, 3.3KHz, & 10KHz,
cut and boost

Phantom Power.....+15VDC, all channel MIC inputs (XLR, from Pin 2 to Pin 1)

Power Supply115 (60Hz) / 230 (50Hz) VAC, selectable

Fuse2 A / 250 V 5 x 20mm, glass type, slow blow

Dimensions20.0" X 8.25" X 11.1" (50.8 X 20.9 X 28.2 cm)

Weight24.05 lbs (10.93 Kg)

The specifications above are correct at the time of printing of this manual. For improvement purposes, all specifications for this unit, including design and appearance, are subject to change without prior notice.