

## SRA Specifications

<b>INPUTS:</b>	ONE XLR JACK & ONE 1/4" TRS PHONE JACK FOR EACH CHANNEL 47 KOHM BALANCED & 40 KOHMS UNBALANCED
<b>OUTPUTS:</b>	ONE 1/4" PHONE JACK & ONE PAIR BINDING POST SCREW TERMINALS FOR EACH CHANNEL <b>SRA 2150:</b> RMS 150W X 2 @ 4 OHMS / BRIDGED RMS 250W @ 8 OHMS <b>SRA 2250:</b> RMS 250W X 2 @ 4 OHMS / BRIDGED RMS 350W @ 8 OHMS
<b>LOWEST OUTPUT LOAD IMPEDANCES:</b>	STEREO: 2 OHMS, BRIDGED: 4 OHMS
<b>FREQUENCY RESPONSE:</b>	5Hz~40KHz, +/- 0.5dB
<b>SIGNAL-TO-NOISE RATIO (IEC-A):</b>	> 94dB
<b>T.H.D.:</b>	< 0.05%
<b>INDICATORS:</b>	POWER/ON, SIGNAL, PEAK, PROTECT
<b>COOLING:</b>	CONVECTION (NO FAN)
<b>FUSE REQUIREMENTS (115V/230V):</b>	<b>SRA 2150:</b> 5X20mm GLASS TUBE, 5A SLOW BLOW <b>SRA 2250:</b> 5X20mm GLASS TUBE, 5A SLOW BLOW
<b>DIMENSIONS:</b>	<b>SRA 2150/2250:</b> 19" x 1.75" x 11.8" (481 X 44 X 300mm), 1U RACK HEIGHT
<b>WEIGHT:</b>	<b>SRA 2150:</b> 14.3 lbs (6.5 Kg) <b>SRA 2250:</b> 16.5 lbs (7.5 Kg)

*For improvement purposes, specifications and design subject to change without prior notice*